

CANALIZZABILE		42QSS009D8S	42QSS012D8S	42QSS018D8S
		42QSS009D8S-1		
Alimentazione	V-ph-Hz	220-240V~, 50Hz, 1Ph	220-240V~, 50Hz, 1Ph	220-240V~, 50Hz, 1Ph
Capacità Raffrescamento	kW	2.64	3.52	5.28
Capacità Riscaldamento	kW	2.64	3.52	5.28
Potenza assorbita nominale	W	130	130	90
Corrente assorbita nominale Max.	A	1.11	1.11	1.20
Livello potenza sonora	dB(A)	60	60	61
Livello pressione sonora (high/med/low)	dB(A)	42/36/30	42/36/30	45/38/33
Portata d'aria (high/med/low)	m ³ /h	580/480/300	580/480/300	880/650/350
Peso (Net/Gross)	kg	18.0 / 22.0	18.0 / 22.0	24.5/29.5
Dimensioni (W×D×H)	mm	700×450×200	700×450×200	880x674x210
Imballo (W×D×H)	mm	860×540×285	860×540×285	1070x725x280
Tubazioni Liquido/Gas	mm(inch)	Φ6.35/Φ9.52 (1/4"/3/8")	Φ6.35/Φ9.52 (1/4"/3/8")	Φ6.35 / Φ12.7 (1/4" / 1/2")

