

GreenLight Plus		42QHC007D8S-1	42QHC009D8S-1	42QHC012D8S	42QHC018D8S	42QHC024D8S-1
		42QHC007D8S	42QHC009D8S			42QHC024D8S
				42QHC012D8IT		42QHC024D8IT
Alimentazione	V-ph-Hz	220-240V~, 50Hz, 1Ph	220~240V / 1Ph / 50Hz	220~240V / 1Ph / 50Hz	220~240V / 1Ph / 50Hz	220~240V / 1Ph / 50Hz
Capacità Raffrescamento	kW	2.05	2.64	3.52	5.28	7.04
Capacità Riscaldamento	kW	2.05	2.64	3.52	5.28	7.04
Potenza assorbita nominale	W	22	22	22	36	60
Corrente assorbita nominale Max.	A	0.5	0.5	0.5	0.5	0.7
Livello potenza sonora	dB(A)	53	53	54	57	63
Livello pressione sonora (high/med/low)	dB(A)	39/35/31/22	39/35/31/22	40/35/31/22	43/39/35/24	48/44/39/29
Portata d'aria (high/med/low)	m <sup>3</sup> /h	440/360/280/150	440/360/280/150	510/420/330/170	750/630/510/330	1100/920/750/450
Peso (Net/Gross)	kg	7.5 / 10.0	7.5 / 10.0	8.5 / 12.0	11.0 / 16.0	13.5 / 18.5
Dimensioni (WxDxH)	mm	730×192×291	730×192×291	812×192×300	973×218×319	1082×225×338
Imballo (WxDxH)	mm	800×275×375	800×275×375	880×275×385	1055×405×305	1165×420×315
Tubazioni Liquido/Gas	mm(inch)	Φ6.35/Φ9.52 (1/4"/3/8")	Φ6.35/Φ9.52 (1/4"/3/8")	Φ6.35/Φ9.52 (1/4"/3/8")	Φ6.35/Φ12.7 (1/4"/1/2")	Φ9.52/Φ15.9 (3/8"/5/8")

