

Information requirements							
This information includes the results of calculation of the seasonal energy consumption and efficiency for air conditioner in regards to ErP pursuant to the Commission Regulation(EU) No.206/2012 and No.626/2011. Information to identify the model(s) to which the information relates to:							
AIR CONDITIONER							
TYPE : MULTI SPLIT							
WALL-MOUNTED							
Indoor unit(s) : 42QHC007D8S-1*4							
Outdoor unit : 38QU5028D8S4							
Brand : CARRIER							
Function (indicate if present)				if function includes heating : Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.			
cooling		Y		Average (mandatory)		Y	
heating		Y		Warmer (if designated)		N	
				Colder (if designated)		N	
Item	symbol	value	unit	Item	symbol	value	unit
Design load				Seasonal efficiency			
cooling	Pdesignc	8,2	kW	cooling	SEER	7,0	-
heating/Average	Pdesignh	6,5	kW	heating/Average	SCOP/A	4,0	-
heating/Warmer	Pdesignh	x,x	kW	heating/Warmer	SCOP/W	x,x	-
heating/Colder	Pdesignh	x,x	kW	heating/Colder	SCOP/C	x,x	-
Declared capacity(*) for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj				Declared energy efficiency ratio(*), at indoor temperature 27(19)°C and outdoor temperature Tj			
Item	symbol	value	unit	Item	symbol	value	unit
Tj = 35°C	Pdc	8,200	kW	Tj = 35°C	EERd	3,23	-
Tj = 30°C	Pdc	6,100	kW	Tj = 30°C	EERd	5,30	-
Tj = 25°C	Pdc	3,901	kW	Tj = 25°C	EERd	9,13	-
Tj = 20°C	Pdc	2,358	kW	Tj = 20°C	EERd	16,04	-
Declared capacity(*) for heating/Average season, at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance(*)/Average season, at indoor temperature 20°C and outdoor temperature Tj			
Item	symbol	value	unit	Item	symbol	value	unit
Tj = -7°C	Pdh	5,75	kW	Tj = -7°C	COPd	2,52	-
Tj = 2°C	Pdh	3,77	kW	Tj = 2°C	COPd	3,88	-
Tj = 7°C	Pdh	2,39	kW	Tj = 7°C	COPd	5,44	-
Tj = 12°C	Pdh	1,73	kW	Tj = 12°C	COPd	6,20	-
Tj = bivalent temperature	Pdh	5,75	kW	Tj = bivalent temperature	COPd	2,52	-
Tj = operating limit	Pdh	6,21	kW	Tj = operating limit	COPd	2,36	-
Declared capacity(*) for heating/Warmer season, at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance(*)/Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Item	symbol	value	unit	Item	symbol	value	unit
Tj = 2°C	Pdh	x,x	kW	Tj = 2°C	COPd	x,x	-
Tj = 7°C	Pdh	x,x	kW	Tj = 7°C	COPd	x,x	-
Tj = 12°C	Pdh	x,x	kW	Tj = 12°C	COPd	x,x	-
Tj = bivalent temperature	Pdh	x,x	kW	Tj = bivalent temperature	COPd	x,x	-
Tj = operating limit	Pdh	x,x	kW	Tj = operating limit	COPd	x,x	-
Declared capacity(*) for heating/Colder season, at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance(*)/Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Item	symbol	value	unit	Item	symbol	value	unit
Tj = -7°C	Pdh	x,x	kW	Tj = -7°C	COPd	x,x	-
Tj = 2°C	Pdh	x,x	kW	Tj = 2°C	COPd	x,x	-
Tj = 7°C	Pdh	x,x	kW	Tj = 7°C	COPd	x,x	-
Tj = 12°C	Pdh	x,x	kW	Tj = 12°C	COPd	x,x	-
Tj = bivalent temperature	Pdh	x,x	kW	Tj = bivalent temperature	COPd	x,x	-
Tj = operating limit	Pdh	x,x	kW	Tj = operating limit	COPd	x,x	-
Tj = -20°C	Pdh	x,x	kW	Tj = -20°C	COPd	x,x	-
Bivalent temperature				Operating limit temperature			
heating/Average	Tbiv	-7	°C	heating/Average	Tol	-15	°C
heating/Warmer	Tbiv	x	°C	heating/Warmer	Tol	x	°C
heating/Colder	Tbiv	x	°C	heating/Colder	Tol	x	°C
Cycling interval capacity				Cycling interval efficiency			
for cooling	Pcycc	x,x	kW	heating/Average	EERcyc	x,x	-
for heating	Pcyh	x,x	kW	heating/Warmer	COPcyc	x,x	-
Degradation co-efficient cooling	Cdc	0,25	-	Degradation co-efficient heating	Cdc	0,25	-
Electric power input in power modes other than 'active mode'				Annual electricity consumption			
off mode	Poff	0,018	kW	cooling	Q _{CE}	410	kWh/a
standby mode	Psb	0,018	kW	heating/Average	Qhe	2275	kWh/a
thermostat-off mode	Pto	0.014/0.03	kW	heating/Warmer	Qhe	x	kWh/a
crankcase heater mode	Pck	0	kW	heating/Colder	Qhe	x	kWh/a
Capacity control(indicate one of the options)				Other items			
Item	symbol	value	unit	Item	symbol	value	unit
fixed		Y/N		Sound power level (indoor/outdoor)	LWA	53/70	dB(A)
staged		Y/N		Global warming potential	GWP	675	kgCO ₂ eq
variable		Y		Rated air flow (indoor/outdoor)		521/3800	m ³ /h
Contact details for obtaining more information	Company: Century Carrier Residential Air Conditioning Equipment Co. Ltd Address: RM5, 5/F, Tower 3, Enterprise Square, 9 Sheung Yuet Road, Kowloon, Hong Kong Telephone: +86-757-26338546 Fax: +86-757-26337977						